## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V	-TAC
----------------------------------	------

Supplier's address: V-TAC Europe Ltd., bul. Rozhen 41, Sofia, BG

Model identifier: 21601

Type of light source	Type	of light	source:
----------------------	------	----------	---------

Lighting technology used:	LED	Non-directional or	NDLS
		directional:	
Light source cap-type	L/N/G Con-		
(or other electric interface)	nection		
Mains or non-mains:	NMLS	Connected light	No
		source (CLS):	
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
Product parameters			

## Product parameters

Froduct parameters				
Parameter		Value	Parameter	Value
General product parameters:				
_ ·	mption in on- 00 h), rounded st integer	40	Energy efficiency class	G
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	3 560 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 400
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	40,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	67	Spectral power dis-	See image
sions without	Width	35	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	1 200	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,313
		nates (x and y)	0,337
Parameters for LED and OLED light sources:			
R9 colour rendering index value	8	Survival factor	0,90
the lumen maintenance factor	0,96		

(a)'-': not applicable; (b)'-': not applicable;

