Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd., bul. Rozhen 41, Sofia, BG

Model identifier: 23139

Type of light source:	Type	of light	source:
-----------------------	------	----------	---------

Type of light source:							
Lighting technology used:	LED	Non-directional or directional:	NDLS				
Light source cap-type	+ve and -ve (be-						
(or other electric interface)	cause strips						
	are DC voltage						
	and have black and red wires)						
Mains or non-mains:	NMLS	Connected light	No				
ividitis of floti-fillatits.	INIVILO	Connected light source (CLS):	NO				
Colour-tuneable light source:	No	Envelope:	-				
High luminance light source:	No						
Anti-glare shield:	No	Dimmable:	Only with spe-				
			cific dimmers				
Product parameters							
Parameter	Value	Parameter	Value				
	General product parameters:						
Energy consumption in on-	5	Energy efficiency	G				
mode (kWh/1000 h), rounded		class					
up to the nearest integer	450:	Canada and and a	4.000				
Useful luminous flux (фuse), indicating if it refers to the flux in	450 in Sphere (360°)	Correlated colour	4 000				
a sphere (360°), in a wide cone	Spriere (300)	temperature, rounded to the near-					
(120º) or in a narrow cone (90º)		est 100 K, or the					
(,		range of correlat-					
		ed colour temper-					
		atures, rounded to					
		the nearest 100 K,					
		that can be set					
On-mode power (P _{on}), ex-	5,0	Standby power (P _{sb}),	0,00				
pressed in W		expressed in W and					
		rounded to the sec- ond decimal					
Networked standby power		Colour rendering in-	80				
(P_{net}) for CLS, expressed in W	_	dex, rounded to the	OU				
and rounded to the second dec-		nearest integer, or					
imal		the range of CRI-val-					
		ues that can be set					
		·	•				

Outer dimen-	Height	5	Spectral power dis-	See image		
sions without	Width	10	tribution in the	in last page		
separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Depth	500	range 250 nm to 800 nm, at full-load			
Claim of equiva	lent power ^(a)	-	If yes, equivalent power (W)	-		
			Chromaticity coordi-	0,384		
			nates (x and y)	0,386		
Parameters for LED and OLED light sources:						
R9 colour rende	ring index value	7	Survival factor	1,00		
the lumen main	tenance factor	0,96				

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

