Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd., bul. Rozhen 41, Sofia, BG

Model identifier: 23335


_	•			
Type	Λt	liaht	COLL	rca.
IVDE	VI.	HEIIL	SOU	LC.

Type of light source:						
Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	+ve and -ve (be-					
(or other electric interface)	cause strips are DC voltage and have black and red wires)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers			
	Product para	meters				
Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	9	Energy efficiency class	F			
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	804 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000			
On-mode power (P _{on}), expressed in W	8,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80			

Outer dimen-	Height	5	Spectral power dis-	See image		
sions without	Width	11	tribution in the	in last page		
separate control gear, lighting control parts and nontrol parts, if any (millimetre)	Depth	500	range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-		
			Chromaticity coordi-	0,384		
			nates (x and y)	0,386		
Parameters for LED and OLED light sources:						
R9 colour rendering index value 7		7	Survival factor	1,00		
the lumen maintenance factor		0,96				

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;



Model placed on the Union market from 13/12/2023



EPREL registration number: 1872568 https://eprel.ec.europa.eu/qr/18

72568

Supplier: V-TAC Europe Ltd (Manufacturer) Website: www.v-tac.eu

Customer care service:

Name: V-TAC Europe Ltd. Website: www.v-tac.eu

Email: office@v-tac.eu Phone: +359290566

Address:

bul. Rozhen 41

Sofia Bulgaria