## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd., bul. Rozhen 41, Sofia, BG

Model identifier: 10233

## Type of light source:

	1		
Lighting technology used:	LED	Non-directional or	DLS
		directional:	
		unectional.	
Light source cap-type	ADAPTOR		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light	No
		U U	
		source (CLS):	
Colour-tuneable light source:	No	Envelope:	-
<b>v</b>		•	
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
, and Blane sinera.		Birinabie:	110

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
•.	nption in on- 00 h), rounded st integer	5	Energy efficiency class	E		
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone nrow cone (90º)	550 in Nar- row cone (90°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	4 000		
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	5,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
(P <sub>net</sub> ) for CLS, e	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	24	Spectral power dis-	See image		
sions without separate con- trol gear, light- ing control	Width Depth	160 26	tribution in the range 250 nm to 800 nm, at full-load	in last page		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	lf yes, equivalent power (W)	-			
		Chromaticity coordi-	0,377			
		nates (x and y)	0,378			
Parameters for directional light sources:						
Peak luminous intensity (cd)	1 526	Beam angle in de- grees, or the range of beam angles that can be set	39			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	11	Survival factor	0,90			
the lumen maintenance factor	0,96					
(a),		,				

(a)'-' : not applicable;

(b)'-' : not applicable;

