Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources	PELEGATED REGUI	LATION (EU) 2019/2	015 with regard to ener	gy labelling of light
Supplier's name	e or trade mark:	V-TAC		
Supplier's addre	ess: V-TAC Europ	e Ltd., bul. Rozhen	41, Sofia, BG	
Model identifie	r: 10238			
Type of light so	urce:			
Lighting technology used:		LED	Non-directional or directional:	DLS
Light source cap-type		ADAPTOR		
(or other electric interface)				
Mains or non-mains:		NMLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance light source:		No		
Anti-glare shield:		No	Dimmable:	No
		Product para	T	ı
Parameter		Value	Parameter	Value
		General product p	T	I
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		12	Energy efficiency class	F
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 100 in Nar- row cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 400
On-mode power (P _{on}), ex- pressed in W		12,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimen-	Height	24	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
sions without separate con- trol gear, light- ing control	Width Depth	273 26		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,313			
		nates (x and y)	0,338			
Parameters for directional light sources:						
Peak luminous intensity (cd)	3 780	Beam angle in degrees, or the range of beam angles that can be set	35			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	11	Survival factor	1,00			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

