Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources	LLLGATED REGOT	AHON (LO) 2013/2	015 with regard to ener	gy labelling of light		
Supplier's name	e or trade mark:	V-TAC				
Supplier's address: V-TAC Europe Ltd., bul. Rozhen 41, Sofia, BG						
Model identifie	r: 10246					
Type of light so	urce:					
Lighting technology used:		LED	Non-directional or directional:	DLS		
Light source cap-type		ADAPTOR				
(or other electric interface)						
Mains or non-mains:		NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	No		
		Product para		1		
Parameter		Value	Parameter	Value		
		General product p		I		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		18	Energy efficiency class	E		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		2 000 in Nar- row cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P _{on}), expressed in W		18,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimensions without separate control gear, lighting control	Height Width Depth	24 378 26	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,432			
		nates (x and y)	0,399			
Parameters for directional light sources:						
Peak luminous intensity (cd)	1 297	Beam angle in degrees, or the range of beam angles that can be set	82			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	11	Survival factor	1,00			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

