## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 2034

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	DC Female		
(or other electric interface)	connector		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consum mode (kWh/100 up to the nearest	0 h), rounded	3	Energy efficiency class	E		
Useful luminous indicating if it re in a sphere (36 cone (120 <sup>°</sup> ) or in (90 <sup>°</sup> )	fers to the flux 0°), in a wide	400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	9 600		
On-mode po expressed in W	ower (P <sub>on</sub> ),	3,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
Networked stand for CLS, express rounded to the s	sed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer	Height	4	Spectral power	See image		
dimensions	Width	9	distribution in the	in last page		
without	Depth	500	]	     Dage 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity	0,100			
		coordinates (x and y)	0,680			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-100	Survival factor	1,00			
the lumen maintenance factor	0,96					
(a).	1					

(a)'-' : not applicable;

(b)'-' : not applicable;

