Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources												
Supplier's name or trade mark: V-TAC Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria Model identifier: 212126												
								Type of light so	urce:			
								Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		+ve and -ve										
(or other electric interface)												
Mains or non-mains:		NMLS	Connected light source (CLS):	No								
Colour-tuneable light source:		No	Envelope:	-								
High luminance light source:		No										
Anti-glare shield:		No	Dimmable:	Only with specific dimmers								
Product parameters												
Parameter		Value	Parameter	Value								
General product parameters:												
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		11	Energy efficiency class	G								
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		900 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500								
On-mode power (P _{on}), expressed in W		11,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00								
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80								
Outer	Height	4	Spectral power	See image								
dimensions	Width	10	distribution in the	in last page								

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	500	range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-			
			Chromaticity	0,307			
			coordinates (x and y)	0,330			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		6	Survival factor	1,00			
the lumen maintenance factor		0,96					

(a)'-': not applicable;

(b)'-': not applicable;

