Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 212148

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	+ve and -ve (because strips are DC voltage and have black and red wires)		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters						
Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	11	Energy efficiency class	G			
Useful luminous flux (ϕ use), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	900 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500			
On-mode power (P _{on}), expressed in W	11,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	_	Colour rendering index, rounded to the nearest integer, or the range of CRI-	80			

			values that can be set			
Outer I	Height	4	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page		
dimensions Width without Depth separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Width	12				
	Depth	500				
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-		
			Chromaticity	0,307		
			coordinates (x and y)	0,330		
Parameters for LED and OLED light sources:						
R9 colour rendering index value		6	Survival factor	1,00		
the lumen maintenance factor		0,96				
(a)						

(a)'-' : not applicable;

(b)'-' : not applicable;

