Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 212459

Type of light source:	Type	of light	source:
-----------------------	------	----------	---------

Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type (or other electric interface)	+ve and -ve (because strips are DC voltage and have black and red wires)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	Only with specific dimmers	
Product parameters				
Parameter	Value	Parameter	Value	
General product parameters:				
Farancia communication in the	10	F		

Parameter	value	Parameter	value		
General product parameters:					
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	10	Energy efficiency class	G		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	830 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode power (P _{on}), expressed in W	10,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	_	Colour rendering index, rounded to the nearest integer, or the range of CRI-	80		

			values that can be set	
Outer	Height	4	Spectral power	See image
dimensions	Width	10	distribution in the	in last page
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	500	range 250 nm to 800 nm, at full-load	
Claim of equival	ent power ^(a)	-	If yes, equivalent power (W)	-
			Chromaticity	0,373
			coordinates (x and y)	0,374
Parameters for LED and OLED light sources:				
R9 colour rende	ring index value	5	Survival factor	1,00
the lumen main	tenance factor	0,96		

(a)'-': not applicable;

(b)_{'-'}: not applicable;

