## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

## Model identifier: 212463

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	+ve and -ve (because strips are DC voltage and have black and red wires)		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters						
Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	17	Energy efficiency class	F			
Useful luminous flux (¢use), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 700 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 400			
On-mode power (P <sub>on</sub> ), expressed in W	17,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-	80			

			values that can be set	
Outer	Height	3	Spectral power	See image
	Width	10	distribution in the	in last page
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	without Depth separate control gear, lighting control parts and non- lighting control parts, if any	500	range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>		-	If yes, equivalent power (W)	-
			Chromaticity	0,311
			coordinates (x and y)	0,336
Parameters for LE	ED and OLED lig	ht sources:	, I	
R9 colour renderi	ng index value	6	Survival factor	1,00
the lumen maintenance factor		0,96		
(-)			· · · ·	

(a)'-' : not applicable;

(b)'-' : not applicable;

