## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 212559

Type of light sou
-------------------

Type of light source:					
Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	+ve and -ve				
(or other electric interface)	(because strips are DC voltage				
	and have black				
	and red wires)				
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Only with		
	Due de et e e e e		specific dimmers		
Product parameters					
Parameter	Value	Parameter	Value		
	General product p	T	_		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	5	Energy efficiency class	F		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	420 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P <sub>on</sub> ), expressed in W	5,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-	80		

			values that can be set			
dimensions W	Height	4	Spectral power distribution in the	See image in last page		
	Width	8				
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	500	range 250 nm to 800 nm, at full-load			
Claim of equival	ent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
			Chromaticity	0,437		
			coordinates (x and y)	0,397		
Parameters for LED and OLED light sources:						
R9 colour rendering index value		3	Survival factor	1,00		
the lumen maintenance factor		0,96				

(a)'-': not applicable;

(b)<sub>'-'</sub> : not applicable;

