Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

commission Delegated Regulation (EU) 2019/2015 with regard to energy labelling of light sources							
Supplier's name or trade mark: V-TAC							
Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria							
Model identifier: 212594							
Type of light source:							
Lighting technology used:		LED	Non-directional or directional:	NDLS			
Light source cap-type		+ve and -ve					
(or other electri	c interface)						
Mains or non-mains:		NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:		No	Envelope:	-			
High luminance light source:		No					
Anti-glare shield:		No	Dimmable:	Only with specific dimmers			
Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		8	Energy efficiency class	D			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 100 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000			
On-mode power (P _{on}), expressed in W		8,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80			
Outer	Height	4	Spectral power	See image			
dimensions	Width	10	distribution in the	in last page			

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	500	range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-		
			Chromaticity	0,372		
			coordinates (x and y)	0,369		
Parameters for LED and OLED light sources:						
R9 colour rendering index value		12	Survival factor	1,00		
the lumen maintenance factor		0,96				

(a)'-': not applicable;

(b)'-': not applicable;

