## **Product Information Sheet**

and rounded to the second dec-

Height

Width

Depth

imal

ing

Outer dimen-

sions without

separate con-

trol gear, light-

control

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC  Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria  Model identifier: 218204								
					Type of light source:			
					Lighting technology used:	LED	Non-directional or directional:	NDLS
					Light source cap-type	Leads		
(or other electric interface)								
Mains or non-mains:	NMLS	Connected light source (CLS):	No					
Colour-tuneable light source:	No	Envelope:	-					
High luminance light source:	No							
Anti-glare shield:	No	Dimmable:	No					
Product parameters								
Parameter	Value	Parameter	Value					
General product parameters:								
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	12	Energy efficiency class	Е					
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 368 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000					
On-mode power (P <sub>on</sub> ), expressed in W	11,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00					
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W	-	Colour rendering in- dex, rounded to the	80					

125

260

55

nearest integer, or the range of CRI-val-

ues that can be set

tribution

Spectral power dis-

range 250 nm to 800

nm, at full-load

in

See image

in last page

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,438	
		nates (x and y)	0,403	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	13	Survival factor	1,00	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;

