## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	s name or	trade mark	: V-TAC
------------	-----------	------------	---------

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 218534

Type	of	light	source:
-,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		0	

Describes Value Describes Value				
	Product para	ameters		
Anti-glare shield:	No	Dimmable:	No	
High luminance light source:	No			
Colour-tuneable light source:	No	Envelope:	-	
Mains or non-mains:	NMLS	Connected light source (CLS):	No	
Light source cap-type (or other electric interface)	L/N/G Con- nection			
Lighting technology used:	LED	Non-directional or directional:	NDLS	

		i rodact parar		I
Parameter		Value	Parameter	Value
General product parameters:				
<u> </u>	nption in on- 00 h), rounded st integer	18	Energy efficiency class	E
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	2 340 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	16,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
(P <sub>net</sub> ) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimensions without separate control gear, lighting control	Height	42	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width	600		
	Depth	100		

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,380
		nates (x and y)	0,380
Parameters for LED and OLED light sources:			
R9 colour rendering index value	0	Survival factor	1,00
the lumen maintenance factor	0,96		

(a)'-': not applicable; (b)'-': not applicable;

