Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V	-TAC
----------------------------------	------

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 218605

trol gear, light-

control

ing

Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		Connector		
(or other electri	ic interface)			
Mains or non-mains:		NMLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance light source:		No		
Anti-glare shield	d:	No	Dimmable:	Yes
		Product para	meters	
Parameter		Value	Parameter	Value
		General product	parameters:	
Energy consur mode (kWh/10 up to the neare	00 h), rounded	4	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	40006500
On-mode power (P _{on}), expressed in W		4,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without	Height	310	Spectral power dis-	See image
	Width	143	tribution in the	in last page
separate control gear, light-	Depth	127	range 250 nm to 800 nm. at full-load	

nm, at full-load

parts and non- lighting con- trol parts, if any (millime- tre)							
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-				
		Chromaticity coordi-	0,440				
		nates (x and y)	0,403				
Parameters for LED and OLED light sources:							
R9 colour rendering index value	53	Survival factor	1,00				
the lumen maintenance factor	0,98						

(a)'-': not applicable; (b)'-': not applicable;

