## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	s name	or trad	le mark:	V-TAC
------------	--------	---------	----------	-------

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 2935

## Type of light source:

Product parameters					
Anti-glare shield:	No	Dimmable:	No		
High luminance light source:	No				
Colour-tuneable light source:	No	Envelope:	-		
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Light source cap-type (or other electric interface)	L/N/G Con- nection				
Lighting technology used:	LED	Non-directional or directional:	NDLS		

Floudet parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		20	Energy efficiency class	E	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		2 580 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000	
On-mode power (P <sub>on</sub> ), expressed in W		17,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen-	Height	100	Spectral power dis-	See image	
sions without	Width	212	tribution in the	in last page	
separate con- trol gear, light- ing control	Depth	165	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,377		
		nates (x and y)	0,377		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	6	Survival factor	0,90		
the lumen maintenance factor	0,96				

(a)'-': not applicable; (b)'-': not applicable;

