Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	s name	or trad	le mark:	V-TAC
------------	--------	---------	----------	-------

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 2951

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	L/N/G Con-				
(or other electric interface)	nection				
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

Froduct parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		20	Energy efficiency class	E		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		2 520 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode power (P _{on}), expressed in W		17,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimensions without separate control gear, lighting control	Height Width	160 160	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page		
	Depth	206				

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,370	
		nates (x and y)	0,369	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	9	Survival factor	0,90	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;

