Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 212653

On-mode

imal

pressed in W

(P_{on}),

power

power

(P_{net}) for CLS, expressed in W

and rounded to the second dec-

Networked standby

Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	+ve and -ve (be-		
(or other electric interface)	cause strips		
·	are DC voltage		
	and have black		
	and red wires)		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe-
			cific dimmers
	Product parar	meters	
Parameter	Value	Parameter	Value
	General product p	arameters:	
Energy consumption in on-	10	Energy efficiency	F
mode (kWh/1000 h), rounded		class	
up to the nearest integer			
Useful luminous flux (фuse), in-	950 in	Correlated colour	4 000
dicating if it refers to the flux in	Sphere (360°)	temperature,	
a sphere (360º), in a wide cone		rounded to the near-	
(120º) or in a narrow cone (90º)		est 100 K, or the	
		range of correlat-	
		ed colour temper-	

10,0

atures, rounded to the nearest 100 K,

Standby power (P_{sb}),

expressed in W and rounded to the sec-

Colour rendering in-

dex, rounded to the

nearest integer, or the range of CRI-val-

ues that can be set

that can be set

ond decimal

0,00

80

Outer dimen-	Height	4	Spectral power distribution in the	See image in last page		
sions without	Width	8				
separate control gear, lighting control parts and nontrol parts, if any (millimetre)	Depth	500	range 250 nm to 800 nm, at full-load			
Claim of equival	lent power ^(a)	-	If yes, equivalent power (W)	-		
			Chromaticity coordi-	0,378		
			nates (x and y)	0,379		
Parameters for LED and OLED light sources:						
R9 colour rendering index value		-3	Survival factor	1,00		
the lumen main	tenance factor	0,96				

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

