Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name	or trade mark:	V-TAC
-----------------	----------------	-------

Supplier's address: V-TAC Europe Ltd., bul. Rozhen 41, Sofia, BG

Model identifier: 10468

_	•			
Type	Λt	liαht	SO	IIrco.
IVDE	VI.	IIGIIL	30	ui ce.

Lighting technology used:	LED	Non-directional or	NDLS
		directional:	
Light source cap-type	CONNECTOR		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light	No
		source (CLS):	
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
Product parameters			

Product parameters

	Froduct parameters			
Parameter		Value	Parameter	Value
		General product p	arameters:	
Energy consummode (kWh/100 up to the neares	00 h), rounded	40	Energy efficiency class	G
Useful luminous dicating if it refe a sphere (360°), (120°) or in a na	ers to the flux in , in a wide cone	3 400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000 or 4 000 or 6 500
On-mode pow pressed in W	ver (P _{on}), ex-	40,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked st (P _{net}) for CLS, e and rounded to imal	•	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	98	Spectral power dis-	See image
sions without	Width	65	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	50	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,380
		nates (x and y)	0,380
Parameters for LED and OLED light sources:			
R9 colour rendering index value	10	Survival factor	0,90
the lumen maintenance factor	0,96		

(a)'-': not applicable; (b)'-': not applicable;

